

# Adhesive Spray detachable

Technical Datasheet

Create Date: 25.06.2013 - Page 1/1

## Introduction

WEICON Adhesive Spray is the clean, quick and easy-to-use adhesives in the spray can. It is particularly suitable for large-surface bonding of light materials to themselves and among each other in craft, model making, do-it-yourself, hobbies and household uses.



Especially suitable for detachable and adjustable joints. Colourless. Neither strikes through nor leaves a wavy surface when working with thin materials.

### Applications

- Fixing of, e. g., templates, promotion boards, posters, photographs, decoration in trade fair construction, layouts and technical drawings (therefore perfect for graphic works)
- Paper, carton and foils can be bonded to themselves and among each other

Detachable joints: When applied on one surface

Permanent joints: When applied on both surfaces

## Technical data

Basis	synthetic rubber
Processing temperature	+ 10 to + 30 °C
Evaporation time	5 to 15 minutes
working time	maximal 60 minutes
Temperature resistance	- 20 to + 65 °C
Coverage per can	about. 13 m <sup>2</sup>

## Processing

1. Shake can before use. Surfaces must be dry, clean and free of grease. Spray onto the surface at about 15 to 30 cm distance. Detachable if a thin adhesive layer is applied on only one surface. For permanent adhesion, Adhesive Spray should be applied either in a thick layer or on both surfaces.
2. Depending on surface characteristics and ambient temperature, let the spray film dry (about 10 minutes) until the adhesive is no longer stringy.
3. Position the parts and join them with strong pressure.

## Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

## Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation.

We do guarantee the continuously high quality of our products.

However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended.

A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

### WEICON GmbH & Co. KG (Headquarter)

Königsberger Str. 255 · DE-48157 Münster  
P.O. Box 84 60 · DE-48045 Münster  
Germany

Tel. +49 (0) 251 / 93 22-0  
Fax +49 (0) 251 / 93 22-244  
Fax +49 (0) 251 / 93 22-233 Export  
www.weicon.de · info@weicon.de

### WEICON Middle East L.L.C.

Jebel Ali Ind Area 3 · P.O. Box 118 216  
Dubai · U.A.E

Phone +971 4 880 25 05  
Fax +971 4 880 25 09  
Mobile +971 50 545 99 83  
www.weicon.ae · info@weicon.ae

### WEICON Inc.

20 Steckle Place · Unit 20  
Kitchener · Ontario · N2E 2C3  
Canada

Phone +1 519 896 5252  
Fax +1 519 896 5254  
Cell +1 519 590 5168  
www.weicon.ca · info@weicon.ca

### WEICON Kimya Sanayi Tic. Ltd. Şti.

Yenibosna Mahallesi Yalçın Koreş Caddesi  
Arifağa Sokak No: 29 Kat: 3  
34530 Yenibosna – İstanbul Turkey  
www.weicon.biz.tr · info@weicon.biz.tr

### WEICON Romania SRL

Str. Depozitelor 22  
540240 Targu Mures, jud. Mures Romania  
www.weicon.com · office@weicon.com