






TECHNICAL DATA SHEET - CST 1180/02 - 23/06/2014

KD 6104

(*)				
T	°C	-100 +250		
p	bar		80	30
V	m/s		2	20
pH		3 + 12		

(*) Avoid the product's use at the maximum temperature and pressure associated values without consult the manufacturer

Composition

- Discontinuous aramid and composite fibers
- PTFE impregnation
- Lubricant silicon free

Features

Braided packing made with combined and twisted aramid composite fibres. The impregnation is done in two stages: firstly during the braiding and secondly on the surface of the finished product.

Applications

Packing suitable for centrifugal and piston pumps, agitators, mixers, widely used in paper mills and sugar industries for miscellaneous applications.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	74,1	243	74,1	110,3
4,0	-	1,0	2,2	41,7	137	41,7	62,1
5,0	3/16	1,0	2,2	26,7	87	26,7	39,7
6,0	-	2,5	5,5	46,3	152	18,5	27,6
6,5	1/4	2,5	5,5	39,4	129	15,8	23,5
8,0	5/16	2,5	5,5	26,0	85	10,4	15,5
9,5	3/8	2,5	5,5	18,5	61	7,4	11,0
10,0	-	2,5	5,5	16,7	55	6,7	9,9
11,0	7/16	2,5	5,5	13,8	45	5,5	8,2
12,0	-	2,5	5,5	11,6	38	4,6	6,9
12,7	1/2	2,5	5,5	10,3	34	4,1	6,2
14,0	9/16	5,0	11,0	17,0	56	3,4	5,1
16,0	5/8	5,0	11,0	13,0	43	2,6	3,9
17,5	11/16	5,0	11,0	10,9	36	2,2	3,2
18,0	-	5,0	11,0	10,3	34	2,1	3,1
19,0	3/4	5,0	11,0	9,2	30	1,8	2,8
22,0	7/8	5,0	11,0	6,9	23	1,4	2,1
25,5	1	5,0	11,0	5,1	17	1,0	1,5

Packaging +/- 10 % in weight; Customized sizes and packaging are available on demand.