

V 9907

COMPOSITION:

- E GLASS FIBER
- GRAPHITE/PTFE IMPREGNATION
- CORROSION INHIBITOR
- LUBRICANT




FEATURES:

6-MICRON GLASS FIBRES, INCREASED TO 9 MICRON THROUGH A SPECIAL PROCESS, AND TWISTED. THIS PACKING IS IMPREGNATED WITH A PARTICULAR COMPOUND BASED ON HIGH PERCENTAGE OF GRAPHITE WITH A SMALL ADDITION OF LUBRICANT AND CORROSION INHIBITOR.

APPLICATIONS:

IS USED ON VALVE STEMS, AS MANHOLE GASKET AND IN STEAM, GAS, FUMES, OILS, ACID AND BASES.

TECHNICAL DATA

(*)				
T	°C	-50/ 500		
p	bar	200		20
V	m/s	1,5		5
pH		2 ÷ 12		

(*) Do not use the product to the maximum temperature and pressure associated without consulting the manufacturer.

in applicazioni con vapore l'impiego è limitato a 350°C

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	1/8	1,0	2,2	74,1	243	74,1	110,3
4	-	1,0	2,2	41,7	137	41,7	62,1
5	3/16	1,0	2,2	26,7	87	26,7	39,7
6	-	2,5	5,5	46,3	152	18,5	27,6
6,5	1/4	2,5	5,5	39,4	129	15,8	23,5
8	5/16	2,5	5,5	26,0	85	10,4	15,5
9,5	3/8	2,5	5,5	18,5	61	7,4	11,0
10	-	2,5	5,5	16,7	55	6,7	9,9
11	7/16	2,5	5,5	13,8	45	5,5	8,2
12	-	2,5	5,5	11,6	38	4,6	6,9
12,7	1/2	2,5	5,5	10,3	34	4,1	6,2
14	9/16	5,0	11,0	17,0	56	3,4	5,1
16	5/8	5,0	11,0	13,0	43	2,6	3,9
17,5	11/16	5,0	11,0	10,9	36	2,2	3,2
18	-	5,0	11,0	10,3	34	2,1	3,1
19	3/4	5,0	11,0	9,2	30	1,8	2,8
22	7/8	5,0	11,0	6,9	23	1,4	2,1
25,5	1	5,0	11,0	5,1	17	1,0	1,5

packaged +/- 10 % in weight

