

C 8100

COMPOSITION:


- CARBON YARN
- GRAPHITE POWDER LOADED LUBRICANTS
- CORROSION INHIBITOR

FEATURES:




BRAIDED PACKING IN PURE ROUND CARBON YARNS, TWISTED TO OBTAIN MAXIMUM FLEXIBILITY UNDER HEAVY LOAD. THIS PACKING IS IMPREGNATED WITH LUBRICANTS SUITABLE FOR HIGH TEMPERATURES AND LOADED WITH GRAPHITE AND MoS_2 .

APPLICATIONS:

PARTICULARLY SUITABLE IN STEAM BOILER FEED WATER PUMPS AND ON VALVES AT LOW TO MEDIUM PRESSURE



TECHNICAL DATA

(*)				
T	°C	-60 +500		
p	bar		100	40
V	m/s		1,5	25
pH		2 ÷ 12		

(*) Do not use the product to the maximum temperature and pressure associated without consulting the manufacturer.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3	1/8	1,0	2,2	101,0	331	101,0	150,5
4	-	1,0	2,2	56,8	186	56,8	84,6
5	3/16	1,0	2,2	36,4	119	36,4	54,2
6	-	2,5	5,5	63,1	207	25,3	37,6
6,5	1/4	2,5	5,5	53,8	176	21,5	32,0
8	5/16	2,5	5,5	35,5	117	14,2	21,2
9,5	3/8	2,5	5,5	25,2	83	10,1	15,0
10	-	2,5	5,5	22,7	75	9,1	13,5
11	7/16	2,5	5,5	18,8	62	7,5	11,2
12	-	2,5	5,5	15,8	52	6,3	9,4
12,7	1/2	2,5	5,5	14,1	46	5,6	8,4
14	9/16	5,0	11,0	23,2	76	4,6	6,9
16	5/8	5,0	11,0	17,8	58	3,6	5,3
17,5	11/16	5,0	11,0	14,8	49	3,0	4,4
18	-	5,0	11,0	14,0	46	2,8	4,2
19	3/4	5,0	11,0	12,6	41	2,5	3,8
22	7/8	5,0	11,0	9,4	31	1,9	2,8
25,5	1	5,0	11,0	7,0	23	1,4	2,1

packaged +/- 10 % in weight

